
DYNAPURE® AS Series

Datasheet



POWERED BY

REDClean® Media

Design | Engineering | Manufacturing | Maintenance | Spare Parts



DynaPure® AS Series

Filter Elements

Technical Data

Materials of Construction

Fan Wheel Aluminum, Backward Inclined

Pedestal, AS-100 thru AS-1000, 3/16" Plate H.R.S. Housing

Inlet cover, Prefilter housing, Drum housing, Perforated filter drum, final filter housing, 16 ga. H.R.S.

Paint Alkyd Enamel

Optional Prefilter Media, 1" Scrim Backed Amerglas

Throaway Liner Media, 9 oz. Polyester Primary Filter Media, 22 oz. Polyester Fiber, Bonded with Acrylic Resin

Secondary Filter Screen, 3/16" Ezy-Kleen Aluminum Mesh (AS-500 thru AS-1000)

Secondary Filter Media, 8 oz. Polyester Foam

VariCel 80-85% ASHRAE (11 3/8" x 23 3/8" x 5 7/8") Optional Final Filters VariCel 90-95% ASHRAE (11 3/8" x 23 3/8" x 5 7/8")

AstroCel 99.97% DOP (11 3/8" x 23 3/8" x 11 1/2")

AS-100 thru AS-600 4" O.D. collar Inlet Size AS-800 thru AS-1000 6" O.D. collar

Shipping Weights (lbs.)							
DynaPure Size	Basic DynaPure	With Optional Prefilter (Note 1)	With Optional Final Filter (Note 1, 2)	With Optional Pre- & Final Filter (Note 1, 2)			
AS-100 AS-200	59	72	75	88			
AS-300	61	74	77	90			
AS-400 AS-600	90	103	106	119			
AS-800	140	162	158	180			
AS-1000	145	167	163	185			

DynaPure Standard Motors [56C Frame, 3450 RPM, and 5/8" Shaft]							
DynaPure Size	HP	Туре	Volts	HZ	PH	Motor Full Load Current, AMPS (Note 3)	
AS-100 AS-200	1/3	TENV	115/230 230/460	60	1 3	7.2/3.6 2.0/1.0	
AS-300 AS-400 AS-600	3/4	TEFC	230/460	60	3	2.8/1.4	
AS-800 AS-1000	3	TEFC	230/460	60	3	9.6/4.8	

DynaPure Optional Motors [56C Frame, and 5/8" Shaft]								
DynaPure Size	HP	Туре	Volts	HZ	PH	RPM	Motor Full Load Current, AMPS (Note 4)	
	1/3	TENV EXPL. PROOF	110/220	50	1	2850	5.2/2.6	
			190/380		3	Z000 L	2.4/1.2	
	(Note 3)		575	60		3450	0.8	
	(Note 3)		115/230		1		8.0/4.0	
			230/460		3		2.0/1.0	
AS-300 AS-400 3/4 AS-600		TEFC	190/380	50	3	2850	3.2/1.6	
	3/4		575	60		3450	1.1	
		EXPL. PROOF	230/460				2.8/1.4	
AS-800 AS-1000	3	TEFC	190/380	50	3	2850	10.4/5.2	
			575	60		3450	3.9	

Notes

- 1. Optional Prefilters and Optional Final Filters shipped separately. Shipping weights are totals for all cartons.
- Add an additional 6 pounds for HEPA (AstroCel) Final Filter.
 1/2 HP may be substituted, dependent on 1/3 HP availability.
- All full load AMPS are average values for several motor manufacturers and should be used only as guide lines for suitable components for the motor branch circuits



aafintl.com

Bringing clean air to life:

American Air Filter Company, Inc. has a policy of continuous product improvement. This document is provided for informal review and establishes no commitment or contract. We reserve the right to change any designs, specifications and products without notice, and we make no warranties regarding the subject matter of this document. Any use, copying or distribution of this document or any part of this document without our permission is prohibited.